

Nebraska Standards Laboratory

3721 West Cuming St. Lincoln, NE 68524 (402)-471-2087

Director of Agriculture Steve Wellman

PO Box 94947 Lincoln, NE 68509-4947 (402) 471-2341

www.nda.nebraska.gov

Calibration Certificate of Mass

August 22, 2022 Calibration Date:

Certificate Number: 2022-114-1

Submitted By: FSCP Area 20 Point of Contact: Kurt Wenninghoff

3721 West Cuming St. Lincoln, NE 68524

Ph. 402-471-3422 email: kurt.wenninghoff@nebraska.gov

PO Number: N/A

Test Item(s): Cast weights

Date Received: August 19, 2022

ID / Asset Number: Area 20 Manufacture: Various

Artifact(s) Description:

Serial Number(s): See Next Page Class Specification: NIST Class F

Material: Cast Iron

Condition: Fair (significant wear)

Reference Standards Used:

Procedure Used:

Equipment Used:

NSL lb standards

NIST HB 6969, SOP 8 (2019) Metrologist:

Mettler XPR32003 Mettler XP 604

JPL

Environmental Cond.

Temp: 22.9 °C Pressure: 733 mmHg

Relative Humidity:

47.3 %

Pertinent Information

• The artifact(s) listed in this document have been found and/or left within the maximum permissible error for the specification stated above, except as noted. An artifact is considered in-compliance when the correction plus the measurement uncertainty is equal to or less than the maximum permissible error. RED print indicates an out-of-compliance reading. It is the decision of the Laboratory to adjust the artifact(s) when the sum of the correction and the uncertainty exceed 95% of the maximum permissible error. All of the tolerances and design specifications (except density, hardness and magnetism) were evaluated according to ASTM E617 (2018) and/or NIST HB 105-1 (2019) for the artifacts designated

- All corrections stated in this report correlate to a "Conventional Mass" (CM), also known as "apparent mass", scale verses 8.0 g/cm³ reference mass density and an air density of 1.2 mg/cm³ at 20 °C.
- It is the end user's responsibility to verify that the weights meet the accuracy requirements outlined in NIST Handbook 44 (2022), Appendix A Fundamental Considerations, when using the weights for calibration of commercial (Legal for Trade) scales.

Traceability Statement

The artifact(s) described in this certificate have been compared to the Standards of the State of Nebraska. The Standards of the State of Nebraska are traceable to the International System of Units (SI) through the National Institute of Standards and Technology (NIST) and are part of a comprehensive measurement assurance program for ensuring continued accuracy and measurement traceability within the level of uncertainty reported by this laboratory. The calibration number for this certificate is the only unique calibration number to be used in referencing measurement traceability for the artifact(s) described in this certificate.

Uncertainty Statement

The combined standard uncertainty includes uncertainties reported for the standard, uncertainties associated with the measurement process, uncertainties for any observed deviations from reference values which are less than surveillance limits and the standard uncertainty for any uncorrected errors associated with air buoyance corrections. The combined standard uncertainty is multiplied by a coverage factor (k), to give the expanded uncertainty, which defines an interval with a 95.45 percent level of confidence. The expanded uncertainty presented in this report is consistent with the Guide to the Expression of Uncertainty in Measurement (2008, revised 2012). Some components of the calibration can be evaluated through a Type A evaluation, or the method of evaluation of uncertainty by the statistical analysis (standard deviation) from the observations taken. Magnetic testing has not been performed, therefore, there are no components for the effects of it in the uncertainty budget.



Nebraska Standards Laboratory

3721 West Cuming St. Lincoln, NE 68524 (402)-471-2087 Director of Agriculture

Steve Wellman P.O. Box 94947 Lincoln, NE 68509-4947 (402) 471-2341 www.nda.nebraska.gov

Calibration Date: August 22, 2022 Certificate Number: 2022-114-1

Conventional Mass Conv	
Nominal Mass Serial Number Conventional Mass Correction (g) Conventional Mass Correction (g) Conventional Mass Correction (g) Conventional Mass Correction (g) (k) factor E (g) (k) factor E (g)	
25 lb WM25-2 0.38 N 0.38 0.14 2 1.1 25 lb WM25-3 0.28 N 0.28 0.14 2 1.1 25 lb WM25-4 1.23 Y -0.01 0.14 2 1.1 25 lb WM25-5 -0.01 N -0.01 0.14 2 1.1 25 lb WM25-6 1.06 Y 0.45 0.14 2 1.1 25 lb WM25-7 1.09 Y 0.41 0.14 2 1.1 25 lb WM25-8 -0.06 N -0.06 0.14 2 1.1 25 lb WM25-9 1.06 Y 0.74 0.14 2 1.1 25 lb WM25-10 0.50 N 0.50 0.14 2 1.1 25 lb WM25-11 0.96 N 0.96 0.14 2 1.1 25 lb WM25-12 1.20 Y 0.36	umed Density (g/cm³)
25 lb WM25-3 0.28 N 0.28 0.14 2 1.1 25 lb WM25-4 1.23 Y -0.01 0.14 2 1.1 25 lb WM25-5 -0.01 N -0.01 0.14 2 1.1 25 lb WM25-6 1.06 Y 0.45 0.14 2 1.1 25 lb WM25-7 1.09 Y 0.41 0.14 2 1.1 25 lb WM25-8 -0.06 N -0.06 0.14 2 1.1 25 lb WM25-8 -0.06 N -0.06 0.14 2 1.1 25 lb WM25-9 1.06 Y 0.74 0.14 2 1.1 25 lb WM25-10 0.50 N 0.50 0.14 2 1.1 25 lb WM25-11 0.96 N 0.96 0.14 2 1.1 25 lb WM25-13 0.54 N 0.54	7.2
25 lb WM25-4 1.23 Y -0.01 0.14 2 1.1 25 lb WM25-5 -0.01 N -0.01 0.14 2 1.1 25 lb WM25-6 1.06 Y 0.45 0.14 2 1.1 25 lb WM25-7 1.09 Y 0.41 0.14 2 1.1 25 lb WM25-8 -0.06 N -0.06 0.14 2 1.1 25 lb WM25-8 -0.06 N -0.06 0.14 2 1.1 25 lb WM25-9 1.06 Y 0.74 0.14 2 1.1 25 lb WM25-10 0.50 N 0.50 0.14 2 1.1 25 lb WM25-11 0.96 N 0.96 0.14 2 1.1 25 lb WM25-12 1.20 Y 0.36 0.14 2 1.1 25 lb WM25-13 0.54 N 0.18	7.2
25 b WM25-5 -0.01 N -0.01 0.14 2 1.1	7.2
25 lb WM25-6 1.06 Y 0.45 0.14 2 1.1 25 lb WM25-7 1.09 Y 0.41 0.14 2 1.1 25 lb WM25-8 -0.06 N -0.06 0.14 2 1.1 25 lb WM25-9 1.06 Y 0.74 0.14 2 1.1 25 lb WM25-10 0.50 N 0.50 0.14 2 1.1 25 lb WM25-11 0.96 N 0.96 0.14 2 1.1 25 lb WM25-12 1.20 Y 0.36 0.14 2 1.1 25 lb WM25-13 0.54 N 0.54 0.14 2 1.1 25 lb WM25-14 0.18 N 0.18 0.14 2 1.1 25 lb WM25-15 0.03 N 0.03 0.14 2 1.1 25 lb WM25-16 -0.68 N -0.68	7.2
25 lb WM25-7 1.09 Y 0.41 0.14 2 1.1 25 lb WM25-8 -0.06 N -0.06 0.14 2 1.1 25 lb WM25-9 1.06 Y 0.74 0.14 2 1.1 25 lb WM25-10 0.50 N 0.50 0.14 2 1.1 25 lb WM25-11 0.96 N 0.96 0.14 2 1.1 25 lb WM25-12 1.20 Y 0.36 0.14 2 1.1 25 lb WM25-13 0.54 N 0.54 0.14 2 1.1 25 lb WM25-14 0.18 N 0.18 0.14 2 1.1 25 lb WM25-15 0.03 N 0.03 0.14 2 1.1 25 lb WM25-16 -0.68 N -0.68 0.14 2 1.1 25 lb WM25-18 0.36 N 0.36	7.2
25 lb WM25-8 -0.06 N -0.06 0.14 2 1.1 25 lb WM25-9 1.06 Y 0.74 0.14 2 1.1 25 lb WM25-10 0.50 N 0.50 0.14 2 1.1 25 lb WM25-11 0.96 N 0.96 0.14 2 1.1 25 lb WM25-12 1.20 Y 0.36 0.14 2 1.1 25 lb WM25-13 0.54 N 0.54 0.14 2 1.1 25 lb WM25-14 0.18 N 0.18 0.14 2 1.1 25 lb WM25-15 0.03 N 0.03 0.14 2 1.1 25 lb WM25-16 -0.68 N -0.68 0.14 2 1.1 25 lb WM25-18 0.36 N 0.55 0.14 2 1.1 25 lb WM25-19 0.47 N 0.47	7.2
25 lb WM25-9 1.06 Y 0.74 0.14 2 1.1 25 lb WM25-10 0.50 N 0.50 0.14 2 1.1 25 lb WM25-11 0.96 N 0.96 0.14 2 1.1 25 lb WM25-12 1.20 Y 0.36 0.14 2 1.1 25 lb WM25-13 0.54 N 0.54 0.14 2 1.1 25 lb WM25-14 0.18 N 0.18 0.14 2 1.1 25 lb WM25-15 0.03 N 0.03 0.14 2 1.1 25 lb WM25-16 -0.68 N -0.68 0.14 2 1.1 25 lb WM25-17 1.28 Y 0.55 0.14 2 1.1 25 lb WM25-18 0.36 N 0.36 0.14 2 1.1 25 lb WM25-19 0.47 N 0.47	7.2
25 lb WM25-10 0.50 N 0.50 0.14 2 1.1 25 lb WM25-11 0.96 N 0.96 0.14 2 1.1 25 lb WM25-12 1.20 Y 0.36 0.14 2 1.1 25 lb WM25-13 0.54 N 0.54 0.14 2 1.1 25 lb WM25-14 0.18 N 0.18 0.14 2 1.1 25 lb WM25-15 0.03 N 0.03 0.14 2 1.1 25 lb WM25-16 -0.68 N -0.68 0.14 2 1.1 25 lb WM25-17 1.28 Y 0.55 0.14 2 1.1 25 lb WM25-18 0.36 N 0.36 0.14 2 1.1 25 lb WM25-19 0.47 N 0.47 0.14 2 1.1 25 lb WM25-20 0.87 N 0.87	7.2
25 lb WM25-11 0.96 N 0.96 0.14 2 1.1 25 lb WM25-12 1.20 Y 0.36 0.14 2 1.1 25 lb WM25-13 0.54 N 0.54 0.14 2 1.1 25 lb WM25-14 0.18 N 0.18 0.14 2 1.1 25 lb WM25-15 0.03 N 0.03 0.14 2 1.1 25 lb WM25-16 -0.68 N -0.68 0.14 2 1.1 25 lb WM25-17 1.28 Y 0.55 0.14 2 1.1 25 lb WM25-18 0.36 N 0.36 0.14 2 1.1 25 lb WM25-19 0.47 N 0.47 0.14 2 1.1 25 lb WM25-20 0.87 N 0.87 0.14 2 1.1	7.2
25 lb WM25-12 1.20 Y 0.36 0.14 2 1.1 25 lb WM25-13 0.54 N 0.54 0.14 2 1.1 25 lb WM25-14 0.18 N 0.18 0.14 2 1.1 25 lb WM25-15 0.03 N 0.03 0.14 2 1.1 25 lb WM25-16 -0.68 N -0.68 0.14 2 1.1 25 lb WM25-17 1.28 Y 0.55 0.14 2 1.1 25 lb WM25-18 0.36 N 0.36 0.14 2 1.1 25 lb WM25-19 0.47 N 0.47 0.14 2 1.1 25 lb WM25-20 0.87 N 0.87 0.14 2 1.1	7.2
25 lb WM25-13 0.54 N 0.54 0.14 2 1.1 25 lb WM25-14 0.18 N 0.18 0.14 2 1.1 25 lb WM25-15 0.03 N 0.03 0.14 2 1.1 25 lb WM25-16 -0.68 N -0.68 0.14 2 1.1 25 lb WM25-17 1.28 Y 0.55 0.14 2 1.1 25 lb WM25-18 0.36 N 0.36 0.14 2 1.1 25 lb WM25-19 0.47 N 0.36 0.14 2 1.1 25 lb WM25-19 0.47 N 0.47 0.14 2 1.1 25 lb WM25-20 0.87 N 0.87 0.14 2 1.1	7.2
25 lb WM25-14 0.18 N 0.18 0.14 2 1.1 25 lb WM25-15 0.03 N 0.03 0.14 2 1.1 25 lb WM25-16 -0.68 N -0.68 0.14 2 1.1 25 lb WM25-17 1.28 Y 0.55 0.14 2 1.1 25 lb WM25-18 0.36 N 0.36 0.14 2 1.1 25 lb WM25-19 0.47 N 0.47 0.14 2 1.1 25 lb WM25-20 0.87 N 0.87 0.14 2 1.1	7.2
25 lb WM25-15 0.03 N 0.03 0.14 2 1.1 25 lb WM25-16 -0.68 N -0.68 0.14 2 1.1 25 lb WM25-17 1.28 Y 0.55 0.14 2 1.1 25 lb WM25-18 0.36 N 0.36 0.14 2 1.1 25 lb WM25-19 0.47 N 0.47 0.14 2 1.1 25 lb WM25-20 0.87 N 0.87 0.14 2 1.1	7.2
25 lb WM25-16 -0.68 N -0.68 0.14 2 1.1 25 lb WM25-17 1.28 Y 0.55 0.14 2 1.1 25 lb WM25-18 0.36 N 0.36 0.14 2 1.1 25 lb WM25-19 0.47 N 0.47 0.14 2 1.1 25 lb WM25-20 0.87 N 0.87 0.14 2 1.1	7.2
25 lb WM25-17 1.28 Y 0.55 0.14 2 1.1 25 lb WM25-18 0.36 N 0.36 0.14 2 1.1 25 lb WM25-19 0.47 N 0.47 0.14 2 1.1 25 lb WM25-20 0.87 N 0.87 0.14 2 1.1	7.2
25 lb WM25-18 0.36 N 0.36 0.14 2 1.1 25 lb WM25-19 0.47 N 0.47 0.14 2 1.1 25 lb WM25-20 0.87 N 0.87 0.14 2 1.1	7.2
25 lb WM25-19 0.47 N 0.47 0.14 2 1.1 25 lb WM25-20 0.87 N 0.87 0.14 2 1.1	7.2
25 lb WM25-20 0.87 N 0.87 0.14 2 1.1	7.2
25 ID WM25-20 0.8/ N 0.8/ 0.14 2 1.1 50 Ib AFC 12 0.00 N 0.00 0.29 2 2.2	7.2
	7.2
	7.2
	7.2
50 lb OPI-C67 -2.45 Y -0.64 0.28 2 2.3 50 lb WM-OPI-C85 -1.48 N -1.48 0.28 2 2.3	7.2
50 lb WM-OPI-C85 -1.48 N -1.48 0.28 2 2.3 1000 lb A-1 13.5 N 13.5 5.8 2.019 45	7.2 7.2
1000 lb A-1 13.5 N 13.5 5.6 2.019 45	7.2
1000 lb A-3 0.1 N 0.1 5.8 2.019 45	7.2
1000 lb A-7 -12.0 N -12.0 5.8 2.019 45	7.2
1000 lb A-8 -29.5 N -29.5 5.8 2.019 45	7.2
1000 lb A-9 -72.0 Y 5.7 5.8 2.019 45	7.2
1000 lb A-10 -21.0 N -21.0 5.8 2.019 45	7.2
1000 lb A-14 -17.5 N -17.5 5.8 2.019 45	7.2
1000 lb A-17 -15.8 N -15.8 5.8 2.019 45	7.2
1000 lb A-18 -11.2 N -11.2 5.8 2.019 45	7.2
1000 lb A-20 -38.6 N -38.6 5.8 2.019 45	7.2
1000 lb 2189 -34.1 N -34.1 5.8 2.019 45	7.2
1000 lb 2190 -4.0 N -4.0 5.8 2.019 45	7.2
1000 lb 2191 -33.5 N -33.5 5.8 2.019 45	7.2
1000 lb 2192 16.1 N 16.1 5.8 2.019 45	7.2
1000 lb 2193 9.7 N 9.7 5.8 2.019 45	7.2
1000 lb 2194 -13.2 N -13.2 5.8 2.019 45	7.2
1000 lb 2195 -28.2 N -28.2 5.8 2.019 45	7.2
1000 lb 2196 6.9 N 6.9 5.8 2.019 45	
1000 lb 2197 -18.7 N -18.7 5.8 2.019 45	7.2

Conversion Factors

1 ounce (avoirdupois) (oz) = 28.349 52 g

1 pound (avoirdupois) (lb) = 453.592 37 g exactly

Jone P. 3

e-signature is copy only

8/25/2022 Date of Issue

Joel P. Lavicky Metrologist Dat

The results in this certificate only applies to those item specifically listed in this certificate. This certificate cannot be considered complete unless it contains <u>all</u> pages. This document may not be reproduced except in <u>full</u>, without the written consent of the Nebraska Standards Laboratory.



DEPARTMENT OF AGRICULTURE

Nebraska Standards Laboratory

3721 West Cuming St. Lincoln, NE 68524 (402)-471-2087

Director of Agriculture

Steve Wellman P.O. Box 94947 Lincoln, NE 68509-4947 (402) 471-2341

www.nda.nebraska.gov

Calibration Certificate of Mass

August 23, 2022 Calibration Date:

Material: Stainless Steel

Submitted By: FSCP Area 20

3721 West Cuming St. Lincoln, NE 68524

Temp: 21.29 °C

Pressure:

Certificate Number:

2022-114-2

Point of Contact: Kurt Wenninghoff

Ph. 402-471-3422

email: kurt.wenninghoff@nebraska.gov

PO Number: N/A

Test Item(s): lb weight kit

Serial Number(s): WM-2D86 Manufacture: Rice Lake Artifact(s) Description:

Date Received: August 19, 2022 ID / Asset Number: Area 20

Class Specification: NIST Class F

Condition: Fair (significant wear)

Reference Standards Used:

NSL lb standards

Environmental Cond.

Procedure Used:

Equipment Used: Sartorius CC10000S

Sartorius CC 1201

Mettler XPR 205 Sartorius CCE6

NIST HB 6969, SOP 8 (2019) Metrologist:

JPL

Relative Humidity:

51.07 %

729.6 mmHg

Pertinent Information

• The artifact(s) listed in this document have been found and/or left within the maximum permissible error for the specification stated above, except as noted. An artifact is considered in-compliance when the correction plus the measurement uncertainty is equal to or less than the maximum permissible error. RED print indicates an out-of-compliance reading. It is the decision of the Laboratory to adjust the artifact(s) when the sum of the correction and the uncertainty exceed 95% of the maximum permissible error. All of the tolerances and design specifications (except density, hardness and magnetism) were evaluated according to ASTM E617 (2018) and/or NIST HB 105-1 (2019) for the artifacts designated class.

- All corrections stated in this report correlate to a "Conventional Mass" (CM), also known as "apparent mass", scale verses 8.0 g/cm³ reference mass density and an air density of 1.2 mg/cm³ at 20 °C.
 - It is the end user's responsibility to verify that the weights meet the accuracy requirements outlined in NIST Handbook 44 (2020), Appendix A Fundamental Considerations, when using the weights for calibration of commercial (Legal for Trade) scales.

Traceability Statement

The artifact(s) described in this certificate have been compared to the Standards of the State of Nebraska. The Standards of the State of Nebraska are traceable to the International System of Units (SI) through the National Institute of Standards and Technology (NIST) and are part of a comprehensive measurement assurance program for ensuring continued accuracy and measurement traceability within the level of uncertainty reported by this laboratory. The calibration number for this certificate is the only unique calibration number to be used in referencing measurement traceability for the artifact(s) described in this certificate.

<u>Uncertainty Statement</u>

The combined standard uncertainty includes uncertainties reported for the standard, uncertainties associated with the measurement process, uncertainties for any observed deviations from reference values which are less than surveillance limits and the standard uncertainty for any uncorrected errors associated with air buoyance corrections. The combined standard uncertainty is multiplied by a coverage factor (k), to give the expanded uncertainty, which defines an interval with a 95.45 percent level of confidence. The expanded uncertainty presented in this report is consistent with the Guide to the Expression of Uncertainty in Measurement (2008, revised 2012). Some components of the calibration can be evaluated through a Type A evaluation, or the method of evaluation of uncertainty by the statistical analysis (standard deviation) from the observations taken. Magnetic testing has not been performed, therefore, there are no components for the effects of it in the uncertainty budget.



DEPARTMENT OF AGRICULTURE

Nebraska Standards Laboratory

3721 West Cuming St. Lincoln, NE 68524 (402)-471-2087 Steve Wellman P.O. Box 94947 Lincoln, NE 68509-4947 (402) 471-2341

www.nda.nebraska.gov

Calibration Date:

August 23, 2022

Certificate Number: 2022-114-2

Calibration Results

Nominal Mass	Serial Number / ID	As Found Conventional Mass Correction (g)	Adjusted (Y/N)	As Left Conventional Mass Correction (g)	Uncertainty ± (g)	(k) factor	NIST Class F MPE ± (g)	Assumed Density (g/cm³)
5 lb	1	-0.082	n	-0.082	0.028	2	0.23	7.84
5 lb	2	-0.110	n	-0.110	0.028	2	0.23	7.8 4
5 lb	3	-0.103	n	-0.103	0.028	2	0.23	7.84
5 lb	4	-0.043	n	-0.043	0.028	2	0.23	7.84
5 lb	5	-0.061	n	-0.061	0.028	2	0.23	7.84
1 lb	1	0.0077	n	0.0077	0.0083	2	0.07	7.84
1 lb	2	0.0316	n	0.0316	0.0083	2	0.07	7.84
1 lb	3	-0.0243	n	-0.0243	0.0083	2	0.07	7.84
1 lb	4	0.0004	n	0.0004	0.0083	2	0.07	7.84
1 lb	5	-0.0283	n	-0.0283	0.0083	2	0.07	7.8 4
0.2 lb		0.0084	n	0.0084	0.0022	2	0.018	7.8 4
0.2 lb	*	0.0082	n	0.0082	0.0022	2	0.018	7.84
0.1 lb		0.0041	n	0.0041	0.0011	2	0.0091	7.84
0.05 lb		0.00170	n	0.00170	0.00054	2	0.0045	7.84
0.02 lb		0.00029	n	0.00029	0.00022	2	0.0018	7.84
0.02 lb	*	0.00022	n	0.00022	0.00022	2	0.0018	7.84
0.01 lb		0.00039	n	0.00039	0.00018	2	0.0015	7.84
8 oz	11	0.0011	n	0.0011	0.0054	2	0.045	7.84
4 oz	13	0.0003	n	0.0003	0.0028	2	0.023	7.84
2 oz		-0.0025	n	-0.0025	0.0013	2	0.011	7.84
1 oz		0.00188	n	0.00188	0.00064	2	0.0054	7.84

Conversion Factors

1 ounce (avoirdupois) (oz) = 28.349 52 g

1 pound (avoirdupois) (lb) = 453.592 37 g exactly

e-signature is copy only

Joel P. Lavicky Metrologist

Data of Issue

The results in this certificate only applies to those item specifically listed in this certificate. This certificate cannot be considered complete unless it contains <u>all</u> pages. This document may not be reproduced except in <u>full</u>, without the written consent of the Nebraska Standards Laboratory.



Nebraska Standards Laboratory 3721 West Cuming St. Lincoln, NE 68524 (402)-471-2087

Director of Agriculture Steve Wellman P.O. Box 94947 Lincoln, NE 68509-4947

(402) 471-2341 www.nda.nebraska.gov

Calibration Certificate of Mass

Calibration Date: August 23, 2022

> FSCP Area 20 Submitted By:

3721 West Cuming St.

Lincoln, NE 68524

Certificate Number:

2022-114-3

Point of Contact: Kurt Wenninghoff

Ph. 402-471-3422

email: kurt.wenninghoff@nebraska.gov

PO Number: N/a

Test Item(s): Metric Weight Kit

Serial Number(s): WM-2-89-4

Condition: Good (some wear) Material: Stainless Steel

Artifact(s) Description:

Date Received: 8/19/2022 ID / Asset Number: Area 20 Class Specification: NIST Class F

Manufacture: Troemner

Equipment Used:

Reference Standards Used:

NSL & /Den Metric Voland-1707

Procedure Used:

NIST HB 6969, SOP 8 (2019) Metrologist:

Sartorius CC 1201 Mettler XPR 205

JPL.

Environmental Cond.

Temp: 21.29 °C

Pressure:

729.6 mmHg

Relative Humidity:

51.07 %

Pertinent Information

- The artifact(s) listed in this document have been found and/or left within the maximum permissible error for the specification stated above, except as noted. An artifact is considered in-compliance when the correction plus the measurement uncertainty is equal to or less than the maximum permissible error. RED print indicates an out-of-compliance reading. It is the decision of the Laboratory to adjust the artifact(s) when the sum of the correction and the uncertainty exceed 95% of the maximum permissible error. All of the tolerances and design specifications (except density, hardness and magnetism) were evaluated according to ASTM E617 (2018) and/or NIST HB 105-1 (2019) for the artifacts designated class.
- All corrections stated in this report correlate to a "Conventional Mass" (CM), also known as "apparent mass", scale verses 8.0 g/cm³ reference mass density and an air density of 1.2 mg/cm³ at 20 °C.
- It is the end user's responsibility to verify that the weights meet the accuracy requirements outlined in NIST Handbook 44 (2020), Appendix A Fundamental Considerations, when using the weights for calibration of commercial (Legal for Trade) scales.

Traceability Statement

The artifact(s) described in this certificate have been compared to the Standards of the State of Nebraska. The Standards of the State of Nebraska are traceable to the International System of Units (SI) through the National Institute of Standards and Technology (NIST) and are part of a comprehensive measurement assurance program for ensuring continued accuracy and measurement traceability within the level of uncertainty reported by this laboratory. The calibration number for this certificate is the only unique calibration number to be used in referencing measurement traceability for the artifact(s) described in this certificate.

Uncertainty Statement

The combined standard uncertainty includes uncertainties reported for the standard, uncertainties associated with the measurement process, uncertainties for any observed deviations from reference values which are less than surveillance limits and the standard uncertainty for any uncorrected errors associated with air buoyance corrections. The combined standard uncertainty is multiplied by a coverage factor (k), to give the expanded uncertainty, which defines an interval with a 95.45 percent level of confidence. The expanded uncertainty presented in this report is consistent with the Guide to the Expression of Uncertainty in Measurement (2008, revised 2012). Some components of the calibration can be evaluated through a Type A evaluation, or the method of evaluation of uncertainty by the statistical analysis (standard deviation) from the observations taken. Magnetic testing has not been performed, therefore, there are no components for the effects of it in the uncertainty budget.



Nebraska Standards Laboratory

3721 West Cuming St. Lincoln, NE 68524 (402)-471-2087

Director of Agriculture Steve Wellman

P.O. Box 94947 Lincoln, NE 68509-4947

(402) 471-2341 www.nda.nebraska.gov

DEPARTMENT OF AGRICULTURE

August 23, 2022 Certificate Number: 2022-114-3 Calibration Date:

Calibration Results

Nominal Mass	Serial Number / ID	As Found Conventional Mass Correction (g)	Adjusted (Y/N)	As Left Conventional Mass Correction (g)	Uncertainty ± (g)	(k) factor	NIST Class F MPE ± (g)	Assumed Density (g/cm³)	
1 kg	1	-0.003	n	-0.003	0.012	2	0.1	7.84	
500 g	2	-0.0121	n	-0.0121	0.0083	2	0.07	7.8 4	
200 g	3	-0.0051	n	-0.0051	0.0048	2	0.04	7.84	
200 g	4	-0.0127	n	-0.0127	0.0048	2	0.04	7.84	
100 g		0.0107	n	0.0107	0.0024	2	0.02	7.84	
50 g		0.0074	n	0.0074	0.0012	2	0.01	7.84	
20 g		0.00091	n	0.00091	0.00048	2	0.004	7.84	
20 g	*	0.00119	n	0.00119	0.00048	2	0.004	7.84	
10 a		-0.00107	n	-0.00107	0.00024	2	0.002	7.84	

Conversion Factors

1 ounce (avoirdupois) (oz) = 28.349 52 g

1 pound (avoirdupois) (lb) = 453.592 37 g exactly

e-signature is copy only

8/25/2022 Date of Issue

Joel P. Lavicky Metrologist

The results in this certificate only applies to those item specifically listed in this certificate. This certificate cannot be considered complete unless it contains all pages. This document may not be reproduced except in full, without the written consent of the Nebraska Standards Laboratory.